IoFClime: The fuzzy logic and the Internet of Things to control indoor temperature regarding the outdoor ambient conditions

Notice: this is the author's version of a work accepted to be published in Future Generation Computer Systems. It is posted here for your personal use and following the Elsevier copyright policies. Changes resulting from the publishing process, such as editing, corrections, structural formatting, and other quality control mechanisms may not be reflected in this document. A more definitive version can be consulted on:

Meana-Llorián, D., González Garca, C., Pelayo G-Bustelo, B. C., Cueva Lovelle, J. M., & Garcia-Fernandez, N. (2016). IoFClime: The fuzzy logic and the Internet of Things to control indoor temperature regarding the outdoor ambient conditions. *Future Generation Computer Systems*. https://doi.org/10.1016/j.future.2016.11.020

© 2016. This manuscript version is made available under the CC-BY-NC-ND 4.0 license http://creativecommons.org/licenses/by-nc-nd/4.0/

IoFClime: The fuzzy logic and the Internet of Things to control indoor temperature regarding the outdoor ambient conditions

Daniel Meana-Llorián^{a,*}, Cristian González García^a, B. Cristina Pelayo G-Bustelo^a, Juan Manuel Cueva Lovelle^a, Nestor Garcia-Fernandez^a

^aUniversity of Oviedo, Department of Computer Science, Sciences Building, C/Calvo Sotelo s/n 33007, Oviedo, Asturias, Spain

Abstract

The Internet of Things is arriving to our homes or cities through fields already known like Smart Homes, Smart Cities, or Smart Towns. The monitoring of environmental conditions of cities can help to adapt the indoor locations of the cities in order to be more comfortable for people who stay there. A way to improve the indoor conditions is an efficient temperature control, however, it depends on many factors like the different combinations of outdoor temperature and humidity. Therefore, adjusting the indoor temperature is not setting a value according to other value. There are many more factors to take into consideration, hence the traditional logic based in binary states cannot be used. Many problems cannot be solved with a set of binary solutions and we need a new way of development. Fuzzy logic is able to interpret many states, more than two states, giving to computers the capacity to react in a similar way to people. In this paper we will propose a new approach to control the temperature using the Internet of Things together its platforms and fuzzy logic regarding not only the indoor temperature but also the outdoor temperature and humidity in order to save energy and to set a more comfortable environment for their users. Finally,

^{*}Corresponding author

Email addresses: danielmeanallorian@gmail.com (Daniel Meana-Llorián),

gonzalezgarciacristian@hotmail.com (Cristian González García), crispelayo@uniovi.es (B. Cristina Pelayo G-Bustelo), cueva@uniovi.es (Juan Manuel Cueva Lovelle), nestor@uniovi.es (Nestor Garcia-Fernandez)

we will conclude that the fuzzy approach allows us to achieve an energy saving around 40% and thus, save money.

Keywords: Internet of Things, Fuzzy Logic, Temperature control,

Temperature sensors

1. Introduction

The Internet of Things (IoT) is a term very popular nowadays. Every day we can listen people taking about Smart Homes [1, 2], Smart Cities [3, 4], Smart Earth [3], and many other kinds of distributed intelligence around heterogeneous and ubiquitous objects. The IoT allows gathering a huge quantity of data that can be processed to help making different decisions. These data may be very varied and confused and processing them might become inoperable.

Humans and computers make decisions in a different way. Whereas human reason uses words, computers use numbers [5]. Moreover, even though the logic applied by humans seems more primitive, they can make better decisions in the real-world when an unexpected problem appears. Computing with words could improve the capability of computers to deal with problems of real-world and thus, improving decision making [5].

The human capability to take decisions without computations is usually referred as 'common sense'. Common sense allows us to take decisions quickly although they are not always the best ones. For example, in the past, we thought that the Earth was flat due to common sense [5]. Moreover, common sense provides a way to get solutions to problems with incomplete or imprecise information whereas classical logic is better to resolve problems well defined. Furthermore, if we always used classical logic, we would take only a few decisions throughout the day.

While classical logic deals with binary sets of values, 0 (false) and 1 (true), fuzzy logic deals with a range of values that represents different degrees of truth on a scale between completely false and completely true [6]. A range of values allows having more states and thus, making decisions knowing more information. For instance, fuzzy logic is able to optimise the moment when collected data should be pushed to a server [6]. Applying classical logic, we would have only two states, push or wait, whereas if we applied fuzzy logic, we could have many states which would indicate the best moment to push data to the server and what data should be pushed.

Our daily life could be benefited with the combination of the IoT and fuzzy logic. For example, local businesses could enhance the management of temperature systems that involve the use of heating systems and air-conditioning systems in order to adapt the indoor conditions taking into consideration the outdoor conditions. Following this path, we would be able to achieve a really Smart City where the indoor locations will be capable of adapting themselves to the outdoor conditions. Using fuzzy logic will allow us to decide the best moment to heat up or to cool down the environment considering the outdoor conditions.

Moreover, fuzzy logic could help to reduce the energy consumption of cities' buildings in order to achieve the zero energy building (ZEBs). The ZEBs are a part of the way towards achieving the Smart Cities [7].

In addition to use fuzzy logic in the IoT, there are also several platforms which allow not only publishing data gathered from our sensors but also consuming data gathered from third-party sensors that could help us to achieve our proposal.

The aim of this research is the development of a prototype that will combine fuzzy logic applied to the IoT and the use of IoT platforms in which the prototype where it will able to consume third-party data. The prototype will be able to automate a system that will control the environmental conditions of a specific place. Moreover, the prototype will address different issues in the world of the IoT like the energy savings and some points of the livability according to [8]. Our goals are the following:

- Consuming data from online open IoT platforms.
- Consuming data from sensors located in microcontrollers like Arduino or

microcomputers like Raspberry Pi and working with actuators located in these devices.

- Setting fuzzy rules to achieve a better performance in the suggested solution.
- Keeping an optimum temperature inside a room for a long time.
- Saving energy. Moreover, this can help to achieve economic savings.
- Achieving some points of the livability.

The remainder of the paper is organised as follows. In Section 2, we will introduce involved topics in this research like fuzzy logic, the IoT, IoT platforms, and the works related with this research. Section 3 will show the case of study, how it works, and how its architecture is. Section 4 will show the software and hardware used in this research. In Section 5 we will cover the evaluation and discussion of the data obtained from comparing the behaviour of our approach with the behaviour of the traditional approach. Section 6 will contain the conclusions of this paper and finally, in Section 7 we will describe the possible future work that can be done from here.

2. State of the Art

The principal aim of this research is to use fuzzy logic in the IoT context. However, before talking about the case study, it is necessary to review the involved concepts. Moreover, inside the IoT context we want to review a special concept, the IoT platforms. These platforms were created to bring the IoT to more people, industry, and researches and thus, to increase the possibilities of the IoT. With these platforms we can intercommunicate objects which are separated by thousands of kilometres or located in places that we cannot imagine. Maybe behind the enemy lines in a battlefield, inside a nuclear plant, in a sealed room full of chemicals or radioactive products, or even in places where they cannot be reached after being set [9, 10]. The fuzzy logic is also a technology presents in many researches. The uses of this technology are multiples and it could be useful in a wide range of fields. For example, the fuzzy logic can be used in the health field achieving the simulation of an artificial pancreas that is able to regulate blood glucose levels in an automatically way [11] or sending health data in the best moment without draining the batteries of the involved devices [12].

In the context of industry, the combination of the IoT and fuzzy logic can help in many situations like controlling the products life cycle [13], monitoring and detecting fires [14], and making decisions about when doing certain procedures in industries [15].

Thus, in this section we will talk about the concepts which are involved in this research: Fuzzy Logic, The Internet of Things, and IoT platforms.

2.1. Fuzzy Logic

The term fuzzy logic was introduced on 1965 by Lotfi Asker Zadeh as a way to deal with common sense problems. He introduced fuzzy sets firstly in [16] and after, fuzzy logic was defined and presented in [17]. Since then, many researches have addressed topics related with fuzzy logic. A frequent issue where fuzzy logic is usually applied is the battery saving. For instance, Larios et al. [18] succeeded in locating a device avoiding many location errors and therefore, reaching a better accuracy. Besides, their approach allows decreasing the energy consumption of different elements like the GPS. Chamodrakas and Martakos [19] proposed to use the fuzzy set representation method to select a network in order to be connected in an efficient way, with a low energy consumption, with a high Quality of Service (QoS), and with good performance. Bagchi [20] used fuzzy logic to keep the quality of playback of multimedia streaming and to achieve improvements in the energy consumption. Cueva-Fernandez et al. [6, 21] made two proposals about how to use fuzzy logic in vehicles. In [6], they proposed the improvement of information exchange between vehicles sensors and servers in order to save energy whereas in [21], they proposed a system to create applications through the voice using fuzzy logic. All of these researches have in common the use of fuzzy logic to make difficult decisions without having clear options to consider.

Fuzzy logic emerged to resolve problems that classical logic cannot address. Classical logic can only deal with binary sets of values (0 or 1), but there are many contexts in which dealing with more values is required. Having more than two values allows having more states and thus, making decisions with more information. These states are usually called linguistic variables and they can represent characteristics like 'size' whose values could be 'small', 'very small', 'big', 'very big', and so on. This approach tries to resolve questions like how big a building is. The answer to this question depends on individual cognition because not everyone would respond the same. For example, for a person who lives in the countryside, a building composed by 6 floors could be big, but for a person who lives in New York, the same building could be small in comparison with the buildings placed in New York.

There are many examples that use fuzzy logic because they need more than two values to represent their states. Grant [11] took the advantages of fuzzy logic to propose a new approach to the diabetic control.

Fuzzy logic allows dealing with vague and ambiguous data in order to make decisions like a person would do it. This logic uses controllers called 'adaptive controllers' [11] or 'expert systems' [22] based in a rules (e.g., if X and Y then Z) to mimic the human fuzzy thinking. These rules represent the knowledge that drives the expert systems to decide optimal decisions. The rules definition is complex and it requires the use of the linguistic variables since the human representation of the knowledge is fuzzy. The process of understanding what a linguistic variable like 'small' means is named fuzzification [23].

2.2. The Internet of Things

In the last years, the interconnection between heterogeneous and ubiquitous objects has been one of the most important issues of researches and business. This interconnection is better known as the Internet of Things [24, 25].

Moreover, the IoT is also one of the most important technologies for the

future according to the ONU in 2005 [24] where the United Nations predicted a new era with more data traffic generated by objects than generated by people. Furthermore, in 2008, the United States National Intelligence Council reported that they considered the IoT as one of the six technologies in which the United States would be more interested in from 2008 to 2025 [26].

However, there is not a standard or unique way to work with the IoT. There are many different platforms to interconnect objects through Internet [27, 28] and a lot of standards to communicate the objects like Near Field Communications (NFC), Radio Frequency Identification (RFID), Bluetooth, or Message Queue Telemetry Transport (MQTT).

The IoT is a set of technologies that can be used for many purposes. The use of sensors in combination with Smart Objects, also called Intelligent Products, and Not-Smart Objects [29] like actuators or other sensors, allows us to read data from the environment and develop a wide range of solutions for many topics. In [29], authors do a review about these Smart and Not-Smart Objects, and introduce some applications that show the wide range of possibilities that the IoT, in combination with Smart and Not-Smart Objects, can offer. Examples of applications of the IoT could be the detection of drowsiness at the wheel through smart devices with many sensors like Smartwatches in order to prevent road accidents [30].

2.3. IoT platforms

Due to the popularity and the growth of the IoT, there have been developed several platforms to interconnect heterogeneous objects through the Internet.

The heterogeneity is a reason for the development of IoT platforms. As it is said in [31], the development of IoT solutions for different Smart Objects from several manufacturers is difficult because of the lack of standards like communication and interconnection protocols. Therefore, they propose a new development model based on handling the user interfaces on the Cloud. By this way, their proposal achieves the development of cross-platform and ubiquitous applications. However, this approach does not take into account the interconnection between objects as other IoT platforms do. There are many platforms and many types and their aims can be very different.

Several platforms were developed for business community like Xively [32] and they allow businesses to be benefited from the IoT advantages in order to connect their products with their users in a safe way, manage their information, improve customer satisfaction, and make new revenue sources.

Many others like ThingSpeak [33] or Paraimpu [34], allow registered users to consume open data in many formats like JSON, CSV, or XML and allow users to share their data from different sources. Both are free but the registrations are controlled by invitations or they require be approved.

There is also an IoT platform called Midgar [27, 28] which generates applications which connect heterogeneous and ubiquitous objects through the Internet in order to facilitate the use of the IoT to any people which do not have computer science knowledge.

In our proposal, we opted for using ThingSpeak and Midgar in order to obtain data from third-party solutions.

2.3.1. ThingSpeak

ThinkSpeak [33] is an open IoT platform for interconnecting objects using web standards. Some of its services are data registration, processing, and distribution; location based services, many plugins, and others useful services. The first thing to do in order to create new objects or services is to choose the device type (Arduino, Netduino, ioBridge, or others) and give the access data (IP, port, subnet mask, and others). This step allows creating a new channel to be used to push the connected devices data, show it, consume it through HTTP requests, or download it in XML, JSON, or CSV format. Moreover, this platform also offers a data accessibility control.

2.3.2. Midgar

Midgar [27, 28] uses a Domain-Specific Language (DSL) called Midgar Object Interconnection Specific Language (MOISL) to generate applications that

interconnect heterogeneous and ubiquitous objects through the Internet. Midgar users can interconnect different objects using a graphic DSL in an easy and fast way. Through this DSL, users can define the application flow in order to connect many objects, read any data from their services, and invoke certain actions in the same objects or in other connected objects. These actions can be different among different objects and one application can interconnect many different objects and invoke different actions. Finally, Midgar processes the model that was defined by the users with MOISL, and creates the application which interconnect the different selected objects and send the different instructions in each circunstance, according to the users definition.

2.4. Related work

There are several commercial solutions that allow handling the temperature of specific places. Two of this solutions are Loxone [35] and tado^{\circ} [36]. Moreover, there are also some researches that combine the IoT and fuzzy logic like Vitruvius [6, 21]

2.4.1. Loxone

Loxone [35] is a home automation system that can control blinds, lights, music systems, or climatisation systems. If we are focused in the temperature, this system has several advantages and disadvantages in comparison with our approach. Some advantages are that it takes into consideration the user geolocation and it registers the temperature to calculate trends and to improve the future work. However, it also has disadvantages like the high buying price and the installation complexity. Moreover, Loxone does not use third-party data whereas our purpose can gather data from online open IoT platforms.

2.4.2. tado°

 $tado^{\circ}$ [36] is a smart thermostat that can be controlled through a web interface or with a smartphone. It can use the user geolocation like Loxone although its installation is easier than Loxone. $tado^{\circ}$ also allows us to save money with a good temperature control. Moreover, it generates detailed reports and it takes into consideration the weather forecast to keep the ambient temperature. The last feature is comparable with the gathering of data from online open IoT platforms so this is a point in common between tado[°] and our proposal. However, there are also disadvantages like the high buying price and it does not automate anything so it cannot be considered smart.

2.4.3. Vitruvius

Vitruvius [6, 21] is a platform which allows users to generate applications in real time that use sensors installed in vehicles. For that purpose, Vitruvius has a web application composed by an application editor that allows designing the applications. Some of available sensors are speed sensors, temperature sensors, and many similar others. Vitruvius combines the IoT with fuzzy logic in order to reduce the push data frequency. Its first versions did not use fuzzy logic, therefore, the data were being pushed to server every second [37]. Due to fuzzy logic, the amount of data pushed were reduced and the data quality and the data analysis performance were improved. However, the use of fuzzy logic makes it harder to detect errors. Whereas Vitruvius used fuzzy logic to automate the pushing of data to server in the best moment to do it, our proposal use the fuzzy logic to automate systems that control the temperature with the intention of adjusting the temperature to obtain a good thermal sensation and thus, save money through the smart approach driven by fuzzy logic.

3. Case study

In this paper we propose a system that controls the temperature of a specific place in an automated way using fuzzy logic. For this purpose, we developed a prototype inspired in the IoT context. The prototype consumes data from sensors and IoT platforms. The sensors were installed in microcontrollers and microcomputers. However, the microcomputers were used not only for consuming data but also for handling the actuators that simulate the temperature control. For this paper, we simulated the temperature control with five LEDs (Figure 1) that represent the next five states in a closed room:



Figure 1: The five LEDs that simulate the temperature control.

- The temperature would be extremely high and the air-conditioning systems would be on at maximum power. This state would be represented by two yellow LEDs.
- The temperature would be high and the air-conditioning systems would be on at normal power. This state would be represented by one yellow led.
- The temperature would be suitable and the heating systems and the airconditioning systems would be off in order to keep the suitable temperature. This state would be represented by the blue led located in the middle.
- The temperature would be low and the heating systems would be on at maximum power. This state would be represented by one red led.
- The temperature would be extremely low and the heating systems would be on at maximum power. This state would be represented by two red LEDs.

Temperature	Humidity (%)																				
(ºC)	0	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100
20	16	16	17	17	17	18	18	19	19	19	19	19	20	20	20	21	21	21	21	21	21
21	18	18	18	19	19	19	19	19	20	20	20	20	21	21	21	22	22	22	22	22	23
22	19	19	19	20	20	20	20	20	21	21	21	21	22	22	22	22	23	23	23	23	24
23	20	20	20	20	21	21	22	22	22	23	23	23	23	24	24	24	24	24	24	25	25
24	21	21	22	22	22	22	23	23	23	24	24	24	24	25	25	25	25	26	26	26	26
25	22	23	23	23	24	24	24	24	24	24	25	25	25	26	26	26	27	27	27	28	28
26	24	24	24	24	25	25	25	26	26	26	26	27	27	27	27	28	28	29	29	29	30
27	25	25	25	25	26	26	26	27	27	27	27	28	28	29	29	30	30	31	31	31	33
28	26	26	26	26	27	27	27	28	28	28	29	29	29	30	31	32	32	33	34	34	36
29	26	26	27	27	27	28	29	29	29	29	30	30	31	33	33	34	35	35	37	38	40
30	27	27	28	28	28	28	29	29	30	30	31	32	33	34	35	36	37	39	40	41	45
31	28	28	29	29	29	29	30	31	31	31	33	34	35	36	37	39	40	41	45	45	50
32	29	29	29	29	30	31	31	33	33	34	35	35	37	39	40	42	44	45	51	51	55
33	29	29	30	30	31	33	33	34	34	35	36	38	39	42	43	45	49	49	53	54	55
34	30	30	31	31	32	34	34	35	36	37	38	41	42	44	47	48	50	52	55		
35	31	32	32	32	33	35	35	37	37	40	40	44	45	47	51	52	55			-	
36	32	33	33	34	35	36	37	39	39	42	43	46	49	50	54	55					
37	32	33	34	35	36	38	38	41	41	44	46	49	51	55							
38	33	34	35	36	37	39	40	43	44	47	49	51	55								
39	34	35	36	37	38	41	41	44	46	50	50	55		1							
40	35	36	37	39	40	43	43	47	49	53	55										
41	35	36	38	40	41	44	45	49	50	55											
42	36	37	39	41	42	45	47	50	52	55											
43	37	38	40	42	44	47	49	53	55												
44	38	39	41	44	45	49	52	55													
45	38	40	42	45	47	50	54	55													
46	39	41	43	45	49	51	55														
47	40	42	44	47	51	54	55							1							
48	41	43	45	49	53	55								-					~		
49	42	45	47	50	54	55															
50	42	45	48	50	55																

Figure 2: Apparent temperature according to the temperature and humidity.

3.1. Temperature control

The developed prototype uses three input values from different IoT sources to make the decisions that control the temperature.

- Outdoor humidity.
- Outdoor temperature.
- Indoor temperature.

The prototype estimates the outdoor apparent temperature using the outdoor humidity, the outdoor temperature, and fuzzy rules. These fuzzy rules were based in the values of the table shown in Figure 2 whose input values are the temperature and the humidity. The output after applying the fuzzy rules are a set of values that indicate the degree of truth of seven linguistic variables that were used in order to represent the apparent temperature. The linguistic variables used were the next fuzzy sets:

- Extremely low: Between -15°C and -5°C.
- Very low: Between -7°C and 3°C.
- Low: Between 0° C and 18° C.
- Normal: Between 14°C and 24°C.
- High: Between 22°C and 30°C.
- Very high: Between 28°C and 38°C.
- Extremely high: Between 35°C and 50°C.

The humidity and the outdoor temperature were also defined using linguistic variables in order to apply fuzzy logic. The outdoor temperature linguistic variables that we used were the same as we used to represent the apparent temperature. Nevertheless, the humidity linguistic variables were the next fuzzy sets:

- Very low: Less than 40%.
- Low: Between 30% and 60%.
- Normal: Between 50% and 70%.
- High: Between 60% and 80%.
- Very high: More than 75%.

From the degree of truth of each linguistic variable we select the centre of gravity in order to take the inputs of the next step. We can see the distribution of the linguistic variables for the outdoor apparent temperature in Figure 3 and for the outdoor humidity in Figure 4.



Figure 3: Distribution of linguistic variables for outdoor apparent temperature.



Figure 4: Distribution of linguistic variables for outdoor humidity.

The outdoor humidity was obtained from an IoT platform that we talked about before, ThingSpeak, and the chosen format was JSON. The outdoor temperature was obtained from a Arduino Uno microcontroller with a temperature sensor connected to the Midgar platform, which was publishing the temperature data in JSON format. The indoor temperature was obtained from a temperature sensor located in a Raspberry Pi 2, where the prototype was running. The indoor temperature linguistic variables were the same as the ones used with the previous temperatures.

After estimating the outdoor apparent temperature, the prototype executes other fuzzy rules whose input is the indoor temperature centre of gravity and the outdoor apparent temperature centre of gravity in order to determine how the actuators should work. The output of these rules are the next linguistic variables and fuzzy sets and it defined the five states that we already mentioned before:

- Heating system at maximum power: Less than 15.
- Heating system at normal power: Between 10 and 20.
- No system running: Between 18 and 22.
- Air condition system at normal power: Between 20 and 30.
- Air condition system at maximum power: More than 25.

After calculating the centre of gravity, we obtained the action to do. All values shown in this section were influenced due to the experience obtained during the research and they should be adjusted to the conditions of each place.

3.2. Architecture

The systems architecture can be divided in the next three layers: **Data** collection, **Data processor**, and **Actuators**. The Figure 5 shows the three layers and their modules. Each layer depends on the others. The first one, **Data collections**, contains the modules which gather data to be processed



Figure 5: System architecture.

from external and local sources. The layer **Data processor** takes the collected data and processes them in order to make decisions. The last layer, **Actuators**, takes the decisions made in the previous layer and routes them to the target actuator in order to do the appropriate action.

3.2.1. Data collection

Our approach requires data from different IoT platforms in order to handle variety data from external sources. The system is prepared to use any platform with minor changes. In our tests we focus in the use of two IoT platforms, one for temperature, Midgar, and another for humidity, ThingSpeak.

The IoT platform used to collect the temperature data was Midgar. Midgar is useful to interconnect Smart Objects in an easy way. In fact, knowledge about languages programming is not necessary [27, 28]. We used Midgar to connect an Arduino Uno with our system through HTTP requests using a REST web service. This Arduino had a temperature sensor that we used to obtain the outdoor temperature.

In order to collect the humidity data, we used another IoT platform, ThingSpeak. This platform allows us to gather the humidity data through HTTP, that other users of the platform had published before.

Our system collects data not only from external sources but also from local sources. We used a Raspberry Pi 2 with a temperature sensor to obtain the temperature of the room where we want to handle the heating and air condition systems.

The data obtained are preprocessed in order to transform it in a common format that the Data processor can handle.

3.2.2. Data processor

The output of the previous layer is a set of properly formatted values that represents the outdoor temperature, the outdoor humidity, and the indoor temperature. These data have to be processed in order to decide what actions to do. For this purpose, we implemented two modules that process the external data and the local data. The external data sources are IoT platforms whereas local data sources are devices located in the room where we want handle the temperature.

In this layer, we convert the concrete values of temperatures and humidity in fuzzy values using the fuzzy sets and linguistic variables that it saw in Section 3.1.

The external processor has fuzzy rules defined to be applied over the fuzzy values previously obtained, which represent the outdoor temperature and humidity. These fuzzy rules are shown in Table 1. With this fuzzy rules we

				Outd	oor tempe	erature		
	AND	Extremely	Very Low	Low	Normal	High	Vory High	Extremely
	mu	Low	Very Low	E0.	Ttorinta	111611	very mgn	High
	Very Low	Extremely	Very Low	Very Low	Normal	Normal	High	Vow High
	very Low	Low	VCI y LOW					very mgn
Outdoor humidity	Low	Extremely	Vory Low	Low	Normal	High	Very High	Extremely
	LOW	Low	Very Low					High
	Normal	Extremely	Vory Low	Low	Normal	Very High	Extremely	Extremely
	Tiorman	Low	Very Low		rormai		High	High
	High	Very Low	Low	Low	Normal	Very High	Extremely	Extremely
	mgn	Very Low	LOW	LOW	worman	very mgn	High	High
	Vory High	Low	Low	Name al	Normal	Extremely	Extremely	Extremely
	very mgn	LOW	LOW	Normai	Normai	High	High	High

Table 1: Fuzzy rules used to calculate the degree of truth of the possible apparent temperature.

obtain the degree of truth of each possible linguistic variable for the apparent temperature.

After applying the fuzzy rules and getting the centre of gravity we obtain a value for apparent temperature. With this value and the indoor temperature, the system is able to make decisions about what action to do in order to handle the rooms temperature. That is why, we apply another set of fuzzy rules, shown in Table 2, whose input are the apparent temperature and the indoor temperature and whose output is the degree of truth of the action to do.

The made decisions are send to the next layer in order to do the corresponding action with the corresponding actuator.

3.2.3. Actuators

The last layer is composed by the actuators that are connected like the heating systems and the air condition systems, although more actuators could be available like fans, LEDs, thermostats, or any others.

The aim of this layer is to route the actions to the corresponding actuators. For example, if the decision made in the Data processor layer was switching on the heating system, the Actuators layer should have switched on the heating system.

		Apparent temperature								
	AND	Extremely Low	Very Low	Low	Normal	High	Very High	Extremely High		
	Extremely	Heating sys. at	Heating sys. at	Heating sys. at	Heating sys. at	Heating sys. at	Heating sys. at	Heating sys. at		
	Low	max. power	max. power	max. power max. power		max. power	max. power	max. power		
	Vow Low	Heating sys. at	Heating sys. at	Heating sys. at	Heating sys. at	Heating sys. at	Heating sys. at	Heating sys. at		
	very Low	max. power	max. power	max. power	max. power	max. power	max. power	max. power		
re	Low	Heating sys. at	Heating sys. at	Heating sys. at	Heating sys. at	Heating sys. at	Heating sys. at	Heating sys. at		
atu		max. power	max power	max. power	normal power	normal power	normal power	normal power		
per	Normal	Heating sys. at	Heating sys. at	Heating sys. at	No system	No system	No system	Air condition sys.		
ten		normal power	normal power	normal power	running	running	running	at normal power		
or	TT:-h	No system	No system	No system	No system	Air condition sys.	Air condition sys.	Air condition sys.		
Inde	mgn	running	running	running	running	at normal power	at normal power	at max. power		
	Vow High	Air condition sys.	Air condition sys.	Air condition sys.	Air condition sys.	Air condition sys.	Air condition sys.	Air condition sys.		
	very mgn	at normal power	at normal power	at normal power	at normal power	at max. power	at max. power	at max. power		
	Extremely	Air condition sys.	Air condition sys.	Air condition sys.	Air condition sys.	Air condition sys.	Air condition sys.	Air condition sys.		
	High	at max. power	at max. power	at max. power	at max. power	at max. power	at max. power	at max. power		

Table 2: Fuzzy rules used to calculate the degree of truth of possible actions to do.

4. Used software and hardware

In order to develop the proposed solution by this paper, we needed the use of different types of software and hardware components.

The developed systems language is Java 8 and it uses the libraries jFuzzy-Logic¹ [38, 39], Pi4J 1.0^2 , and Gson $2.3.1^3$.

The used hardware was an Arduino UNO with a TMP36 temperature sensor and a Raspberry Pi 2 with several electronic components connected to its GPIOs:

- TMP36 temperature sensor.
- MCP3008 analogic-to-digital converter.
- 2 yellow LEDs, 2 red LEDs, and 1 RGB LED.
- Several resistors.

 $^{^1 \}rm jFuzzyLogic: http://jfuzzylogic.sourceforge.net/html/index.html <math display="inline">^2 \rm Pi4J: http://pi4j.com$

³Gson: https://github.com/google/gson

5. Evaluation and discussion

This paper proposes a system to control the temperature in an automated and efficient way. Traditional thermostats control the temperature switching on and switching off the heating system or the air condition system when the temperature is higher or lower than a specific value which is set manually. For instance, a thermostat could be set to switch on the heating system when the temperature is lower than 20°C. The problem is when the temperature is changing near 20°C (e.g., between 19°C and 21°C), because the system would switch on and switch off constantly. The use of fuzzy sets and linguistic variables allows us to determine ranges in which the temperature is suitable. Moreover, we are able to determine the best moment when heating systems and air condition systems have to be switched on and switched off taking the outdoor ambient conditions and using fuzzy logic.

In order to illustrate this, we made an evaluation of our approach where we compared the times that a heating system and an air condition system was switched on and switched off using an old thermostat with using our new fuzzy approach that also takes into account the outdoor conditions and the indoor temperature. In Table 3, it is shown the outdoor temperature, humidity, and the indoor temperature that we used to do the simulation in this evaluation.

We calculated the apparent temperature using the outdoor temperature and humidity, in order to use it with the indoor temperature to determine the best moment to switch on and to switch off the heating system and the air condition system. In Figure 6 we can see the three temperatures used in the evaluation. The blue curve is the outdoor temperature, the yellow curve is the apparent temperature calculated from outdoor temperature and humidity, and the orange curve is the temperature. The apparent temperature and the outdoor temperature are different because the humidity was variable and the apparent temperature is calculated from outdoor temperature and humidity.

The old heating system that we simulate in this evaluation had two heating

Time	Humidity	Temp. Outdoor	T. Indoor
00:00	66	15	18
01:00	69	14	17
02:00	73	12	16
03:00	75	11	15
04:00	76	10	15
05:00	78	9	14
06:00	76	9	14
07:00	74	9	14
08:00	72	10	14
09:00	62	12	15
10:00	53	15	15
11:00	44	17	15
12:00	38	19	18
13:00	33	21	20
14:00	28	23	23
15:00	28	24	23
16:00	29	25	24
17:00	30	26	26
18:00	36	27	26
19:00	40	27	26
20:00	42	28	26
21:00	33	25	23
22:00	30	23	22
23:00	34	20	20

Table 3: Ambient conditions of a full day.



Figure 6: The obtained temperatures for the evaluation.

stages and the old air condition system had two airflow stages to control the temperature. The configuration used is the next:

- Heating system at maximum power: Below 15°C.
- Heating system at normal power: Between 15°C and 17 °C.
- Air condition system at maximum power: Above 25°C.
- Air condition system at normal power: Between 23°C and 25°C.
- Both systems switched off: Between 18°C and 22 °C.

The new fuzzy systems used another configuration based in ranges instead of single values. The used ranges are the same as the fuzzy sets shown in Section 3.1.

After configuring the systems with the obtained and calculated values, we simulated what would have happened if these systems were used in the same conditions. In Figure 7, we can see when the systems switched on and when they switched off. The old heating system switched on one hour before our



Figure 7: Stages of each system for one day.

approach and it also switched off one hour later. Moreover, our approach for air condition system did not use the maximum power whereas the old system was at maximum power during 4 hours. Also, the new air condition system started working 4 hours later and stopped working 1 hour before.

Figure 7 shows how the stages changed during a day and Figure 8 shows how many hours each system was switched on and switched off. We can see that our approach was off for more hours.

Firstly, the old heating system was on for 11 hours whereas the new heating system was on for 8 hours. There were 3 hours or approximately 27.27% of energy saving. And secondly, the old air condition system was on for 8 hours whereas the new air condition system was off for 21 hours so there were 5 hours or approximately 62.5% of energy saving. Therefore, we can assume that there was a certain saving energy.

These results must be interpreted carefully. In spite of defining a temperature ranges, the system did not switch on whenever the temperature was out of range. Therefore, this approach may not be used in context of critical situations



Figure 8: The number of hours per state.

when the control of temperature cannot have margin of errors. The explanation of this behaviour could be the use of external conditions. Considering external conditions may be a good idea for the temperature control in rooms where there are people or objects that need specific environmental conditions. It could be a way of adapting the room for people who are entering and leaving the room. However, there are a lot of situations that this approach could be used.

6. Conclusions

The future of computers is related with the IoT and each progress is very important for the development of technologies from the IoT context. In this paper we presented our approach about the integration of fuzzy logic into the IoT context.

We have proposed the use of fuzzy logic in order to control the temperature of a specific room taking into consideration the outdoor conditions, specifically, the outdoor temperature and humidity to obtain the outdoor apparent temperature.

In order to obtain the outdoor data, we required devices that analyse the environment. These devices can be part of a Smart City or Smart Town, or they can be part of a set of nearby Smart Cities and Smart Towns.

With this data, the developed prototype simulates the control of the heating system and the air condition system so that they could be switched on and switched off considering the combination of outdoor conditions and indoor temperature.

In the evaluation of our proposal, we realised that using fuzzy logic to help systems that control the temperature allows us to save energy and thus, save money. For instance, we achieve an energy saving of around 40% if we understand that time saving implies energy saving. However, fuzzy logic causes that the range in which the systems are off was too broad. Therefore, this approach would not be valid in the context of critical situations where the temperature would be an accurate value due to the consideration of external conditions in addition to local conditions.

7. Future work

The aim of this research was to reach a first approach that combines IoT technologies and fuzzy logic in order to improve the temperature control in specific locations, and from here, there are much work to do in future researches.

- Improving the fuzzy logic configuration: The configuration used in this paper is based in our experience during the research progress. Improving this configuration would allow getting better results, saving more energy, and reaching a better temperature control.
- Saving old temperatures in order to know if the temperature is rising or it is decreasing: The actual approach does not take into consideration indoor temperature history. Knowing the previous temperatures helps the system to make better decisions. The system behaviour may not be the same if the temperature is rising or if it is decreasing. Taking into consideration the temperature progress could help avoid changing the state constantly.

- Publishing the data in IoT platforms: In this research we obtained the outdoor apparent temperature combining the outdoor temperature and humidity. The apparent temperature is a valued data and publishing it could be a good contribution.
- Adding more sensors: In this paper we used three values, the outdoor temperature, the outdoor humidity, and the indoor temperature. Taking more values would allow us to improve the calculation of the apparent temperature. Moreover, we also may calculate the apparent indoor temperature which depends not only on humidity and temperature but also on the quantity of people in the room and many other factors.
- Creating a Domain-Specific Language in order to personalise the rules and the fuzzy sets in an easy way: The fuzzy logic configuration depends on the location and on the people who is going to use the system, thus, adding a way of personalising the configuration for people who does not have knowledge about programming is a great improvement of this research. Developing a Domain-Specific Language (DSL) is the best solution to reach this proposal. A DSL may allow any user with minimum knowledge about computers, to personalise the system configuration.

8. Acknowledgements

This work was performed by the 'Ingeniería Dirigida por Modelos MDE-RG' research group at the University of Oviedo under Contract No. FC-15-GRUPIN14-084 of the research project 'Ingenierá Dirigida Por Modelos MDE-RG'. Project financed by PR Proyecto Plan Regional.

References

 H. G. H. Gu, D. W. D. Wang, A content-aware fridge based on rfid in smart home for home-healthcare, in: 2009 11th International Conference on Advanced Communication Technology, Vol. 02, 2009, pp. 987–990.

- [2] K. a. Hribernik, Z. Ghrairi, C. Hans, K.-D. Thoben, Co-creating the internet of things - first experiences in the participatory design of intelligent products with arduino, in: 2011 17th International Conference on Concurrent Enterprising, 2011, pp. 1–9.
- [3] L. Hao, X. Lei, Z. Yan, Y. ChunLi, The application and implementation research of smart city in china, in: 2012 International Conference on System Science and Engineering (ICSSE), 2012, pp. 288-292. doi:10.1109/ICSSE.2012.6257192.
 URL http://ieeexplore.ieee.org/lpdocs/epic03/wrapper.htm? arnumber=6257192
- [4] R. Lea, M. Blackstock, Smart cities: An iot-centric approach, in: Proceedings of the 2014 International Workshop on Web Intelligence and Smart Sensing, IWWISS '14, ACM, New York, NY, USA, 2014, pp. 12:1—-12:2. doi:10.1145/2637064.2637096. URL http://doi.acm.org/10.1145/2637064.2637096
- [5] M. Nikravesh, Evolution of fuzzy logic: From intelligent systems and computation to human mind, Studies in Fuzziness and Soft Computing 217 (2) (2007) 37-53. doi:10.1007/978-3-540-73182-5_3.
 URL http://dx.doi.org/10.1007/s00500-007-0192-9
- [6] G. Cueva-Fernandez, J. Pascual Espada, V. García-Díaz, R. Gonzalez-Crespo, Fuzzy decision method to improve the information exchange in a vehicle sensor tracking system, Applied Soft Computingdoi:10.1016/j.asoc.2015.01.066.
 URL http://www.sciencedirect.com/science/article/pii/ S1568494615000873
- [7] A. Kylili, P. A. Fokaides, European smart cities: The role of zero energy buildings, Sustainable Cities and Society 15 (2015) 86–95. doi:10.1016/j.scs.2014.12.003.

URL http://www.sciencedirect.com/science/article/pii/ S2210670714001383

- [8] U.S. Department of Transportation, Livability (2015).URL https://www.transportation.gov/livability/101
- [9] N. Bulusu, D. Estrin, L. Girod, Scalable coordination for wireless sensor networks: self-configuring localization systems, in: Proc. of the 6th International Symposium on Communication Theory and Applications(ISCT A 01), Ambleside, UK, no. July, 2001, pp. 1–6.
 URL http://gicl.cs.drexel.edu/people/regli/Classes/CS680/

Papers/SensorNets/iscta-2001.pdf

- [10] I. F. Akyildiz, W. Su, Y. Sankarasubramaniam, E. Cayirci, A survey on sensor networks, IEEE Communications Magazine 40 (8) (2002) 102-105. doi:10.1109/MCOM.2002.1024422. URL http://ieeexplore.ieee.org/lpdocs/epic03/wrapper.htm? arnumber=1024422
- [11] P. Grant, A new approach to diabetic control: Fuzzy logic and insulin pump technology, Medical Engineering & Physics 29 (7) (2007) 824-827. doi:http://dx.doi.org/10.1016/j.medengphy.2006.08.014. URL http://www.sciencedirect.com/science/article/pii/ S1350453306001834
- S. S. Bhunia, S. K. Dhar, N. Mukherjee, ihealth: A fuzzy approach for provisioning intelligent health-care system in smart city, in: 2014 IEEE 10th International Conference on Wireless and Mobile Computing, Networking and Communications (WiMob), 2014, pp. 187–193. doi:10.1109/WiMOB.2014.6962169.

URL http://ieeexplore.ieee.org/lpdocs/epic03/wrapper.htm? arnumber=6962169

[13] R. Y. Chen, Intelligent iot-based tracing system for backward design using fcm and fuzzy rule, in: 2013 Fourth Global Congress on Intelligent Systems, 2013, pp. 229-233. doi:10.1109/GCIS.2013.43.

URL http://ieeexplore.ieee.org/lpdocs/epic03/wrapper.htm? arnumber=6805940

- [14] M. Maksimović, V. Vujović, B. Perišić, V. Milošević, Developing a fuzzy logic based system for monitoring and early detection of residential fire based on thermistor sensors, Computer Science and Information Systems (00) (2014) 90.
- [15] Z. Zinonos, C. Chrysostomou, V. Vassiliou, Wireless sensor networks mobility management using fuzzy logic, Ad Hoc Networks 16 (0) (2014) 70-87. doi:10.1016/j.adhoc.2013.12.003.
 URL http://www.sciencedirect.com/science/article/pii/ S1570870513002850
- [16] L. Zadeh, Fuzzy sets, Inf and Control 8 (1965) 338–353. doi:10.1109/2.
 53.
- [17] L. A. Zadeh, Fuzzy logic and approximate reasoning, Synthese 30 (3-4) (1975) 407-428. doi:10.1007/BF00485052.
 URL http://dx.doi.org/10.1007/BF00485052
- [18] D. F. Larios, J. Barbancho, F. J. Molina, C. León, Lis: Localization based on an intelligent distributed fuzzy system applied to a wsn, Ad Hoc Networks 10 (3) (2012) 604-622. doi:10.1016/j.adhoc.2011.11.003.
 <u>URL</u> http://www.sciencedirect.com/science/article/pii/ S1570870511002095
- [19] I. Chamodrakas, D. Martakos, A utility-based fuzzy topsis method for energy efficient network selection in heterogeneous wireless networks, Applied Soft Computing Journal 12 (7) (2012) 1929–1938. doi:10.1016/j.asoc.2012.04.016. URL http://www.sciencedirect.com/science/article/pii/ S1568494612001998

- [20] S. Bagchi, A fuzzy algorithm for dynamically adaptive multimedia streaming, ACM Transactions on Multimedia Computing, Communications, and Applications 7 (2) (2011) 1–26. doi:10.1145/1925101.1925106.
 URL http://dl.acm.org/citation.cfm?id=1925101.1925106
- [21] G. Cueva-Fernandez, J. Pascual Espada, V. García-Díaz, R. González Crespo, N. Garcia-Fernandez, Fuzzy system to adapt web voice interfaces dynamically in a vehicle sensor tracking application definition, Soft Computingdoi:10.1007/s00500-015-1709-2.
 URL http://link.springer.com/10.1007/s00500-015-1709-2
- [22] S. Russell, P. Norvig, Artificial intelligence: a modern approach.
- [23] E. Portmann, A. Andrushevich, R. Kistler, A. Klapproth, Prometheus fuzzy information retrieval for semantic homes and environments, in: 3rd International Conference on Human System Interaction, HSI'2010 - Conference Proceedings, 2010, pp. 757–762. doi:10.1109/HSI.2010.5514482.
- [24] L. Atzori, A. Iera, G. Morabito, The internet of things: A survey, Computer Networks 54 (15) (2010) 2787-2805. doi: 10.1016/j.comnet.2010.05.010. URL http://www.sciencedirect.com/science/article/pii/ S1389128610001568
- [25] Lu Tan, Neng Wang, Future internet: The internet of things, in: 2010 3rd International Conference on Advanced Computer Theory and Engineering(ICACTE), Vol. 5, IEEE, 2010, pp. V5-376-V5-380. doi:10.1109/ICACTE.2010.5579543. URL http://ieeexplore.ieee.org/lpdocs/epic03/wrapper.htm? arnumber=5579543
- [26] National Intelligence Council, Discruptive civil tehnologies six tehnologies with potential impacts on us interests out to 2025 (2008). URL http://www.dni.gov./nic/confreports_discruptive_tech.html

- [27] C. González García, B. C. Pelayo G-Bustelo, J. Pascual Espada, G. Cueva-Fernandez, Midgar: Generation of heterogeneous objects interconnecting applications. a domain specific language proposal for internet of things scenarios, Computer Networks 64 (2014) 143–158. doi:10.1016/j.comnet. 2014.02.010.
- [28] C. González García, J. Pascual Espada, E. R. Núñez valdez, V. García-Díaz, Midgar : Domain-specific language to generate smart objects for an internet of things platform.
- [29] C. González García, D. Meana-Llorián, C. Pelayo G-Bustelo, J. M. Cueva Lovelle, A review about Smart Objects, Sensors, and Actuators, International Journal of Interactive Multimedia and Artificial Intelligence 4 (3) (2017) 7. doi:10.9781/ijimai.2017.431. URL http://www.ijimai.org/journal/sites/default/files/ files/2016/08/ijimai20174{_}3{_}1{_}pdf{_}15525.pdfhttp: //www.ijimai.org/journal/node/1331
- [30] S. Rios-Aguilar, J. L. M. Merino, A. Millán Sánchez, Á. Sánchez Valdivieso, Variation of the Heartbeat and Activity as an Indicator of Drowsiness at the Wheel Using a Smartwatch, International Journal of Interactive Multimedia and Artificial Intelligence 3 (3) (2015) 96. doi:10.9781/ijimai.2015.3313. URL http://www.ijimai.org/JOURNAL/sites/default/files/ files/2015/06/ijimai20153{_}3{_}13{_}pdf{_}21406.pdfhttp:

//www.ijimai.org/journal/node/787

[31] J. Iglesias Feijoo, G. Amat Gomariz, New Challenges on Crossplatform Digital Contents, International Journal of Interactive Multimedia and Artificial Intelligence 3 (2) (2015) 26. doi:10.9781/ijimai.2015.323. URL http://www.ijimai.org/JOURNAL/sites/default/files/files/ 2015/02/ijimai20153{_}2{_}3.pdfhttp://www.ijimai.org/journal/ node/733

- [32] Xively by logmeinxively. URL https://xively.com/
- [33] Internet of things thingspeak. URL https://www.thingspeak.com/
- [34] Paraimpu: Connect, compose, share. the social tool for the internet of things. URL https://www.paraimpu.com/
- [35] Loxone smart home. easily controlled. intelligently automated. loxone. URL http://www.loxone.com/enen/start.html
- [36] For heating & air conditioning intelligent climate control tado. URL https://www.tado.com/gb/
- [37] G. Cueva-Fernandez, J. Pascual Espada, V. García-Díaz, C. González García, N. Garcia-Fernandez, Vitruvius: An expert system for vehicle sensor tracking and managing application generation, Journal of Network and Computer Applications 42 (2014) 178–188. doi:10.1016/j.jnca.2014.02.013. URL http://dx.doi.org/10.1016/j.jnca.2014.02.013
- [38] P. Cingolani, J. Alcalá-Fdez, jfuzzylogic: a java library to design fuzzy logic controllers according to the standard for fuzzy control programming (2013) 61–75.
- [39] P. Cingolani, J. Alcala-Fdez, jfuzzylogic: a robust and flexible fuzzy-logic inference system language implementation, in: Fuzzy Systems (FUZZ-IEEE), 2012 IEEE International Conference on, IEEE, 2012, pp. 1–8.

View publication stats